

Datasheet for Information Kiosk-----Smart Mivaan 2620---32

| S.N o | Parts | Brand | Specification |
|-------|--------------|------------|-------------------------------------|
| 1 | Equipment | Smart | 1. Cold-rolled CRCA steel plate, |
| | Cabinet | Mivaan2620 | solid, firm and steady, will not be |
| | | 32 | deformed in high temperature |
| | | | and high-cold environment; |
| | | | 2. High technological thermoset |
| | | | powder coating outside and |
| | | | inside, rust & water proof, |
| | | | durable and corrosion resistant; |
| | | | 3. Modular orbit design, |
| | | | extremely convenient for |
| | | | maintenance; |
| | | | 4. Internal wiring with plastic tag |
| | | | lock or trunking, power cord and |
| | | | communication cables tied and |
| | | | buckled up neat and |
| | | | standardized. |
| | | | 5. Floor Mounting. |
| 2 | Display | 320WTP | Size: 32" LED/ Definition: |
| | | | 1920x1080 FHD/ A+ Grade |
| | | | Display/ Response time: 20ms/ |
| | | | Brightness: 250cd/m2/ Contrast |
| | | | Ratio: 3000:1/Scanning frequency: |
| | | | 75Hz/ Interface Type: HDMI |
| 3 | Touch screen | 320WTP | Capacitive Touch/ Resolution: |
| | | | 4096*4096/ Speed of Response: |
| | | | <10ms/ Voltage: DC+5V±5%/ |
| | | | Working Curren:<200mA/ Touch |
| | | | Points: 10 Points/ Touch Method: |
| | | | Finger, Touch Pen/ Interface Type: |
| | | | USB/ Operating Temperature:- |
| | | | 20°C~60°C |
| | | | |

No.8/1Karuvalur Mariamman Koil Street, Udayampalayam, Coimbatore— 641028.Mob:9894761734



| 4 | CPU | Intel Core i5 processor |
|----|----------------------|---|
| 5 | Memory | 8GB and 500 SSD |
| 6 | Optical Device Drive | Provision to connect external CD/DVD ROM |
| 7 | Storage | Integrated Dual port SATA Controller HDD 1 TB 7200 RPM or higher |
| 8 | OS | UBUNTU 14.04 |
| 9 | Network | Integrated Gigabit Ethernet Controller with IPv6 complaint. Ethernet 10/100 Mbps or higher, |
| | | VGA/HDMI/Display Port out. |
| 10 | Wireless | 802.11 or higher |
| 11 | Cooling | Suitable 2 no. of fans to be provided |
| | | inside the chasis. |
| 12 | UPS | Inbuilt UPS 600 VA with 30 minutes |
| | | backup on full load at 0-6 PF |
| 13 | Module | 1 x mini PCIE-half port for Wi-Fi |
| 14 | Power | Input - DC100-240V AC/SO-60H2 |
| | | Output - DC +9V+36V, recommend 12V/5A |
| | | Rated Power: 250W; Safety Standard:3C |
| 15 | Switch | 1 x Power On/on Switch |
| 16 | Button | 1 x ATX /AT quick switch |
| 17 | USB | 2 x USB 2.0 , 1 x USB 3.0 |
| 18 | Power Cord | 1 x 2.5m power cord |
| 19 | Display | 1 x HDMI |
| 20 | LAN | 1 x GbE RJ45 LAN |
| 21 | Audio Port | 1 x AUX |



22. Product Image23 Product Colour



Frame - Black & White

No.8/1Karuvalur Mariamman Koil Street, Udayampalayam, Coimbatore— 641028.Mob:9894761734